



ACTIVE ROLLER GUIDE SYSTEM

elevators
escalators
autowalks



**ACTIVE
ROLLER
GUIDE**

SYSTEM

R

A

Fujitec continuously pursues technological improvements in ride safety, quality, performance and dependability. The addition of the **Active Roller Guide (ARG)** system effectively decreases the amount of vibration felt by passengers during travel. Ideal for high-rise and high-speed applications, smooth and fluid transportation reassures passengers' perception of safety and comfort on a daily basis.


How It Works

Fujitec's **ACTIVE ROLLER GUIDE (ARG)** includes a sensor that detects lateral vibration as the elevator moves through the hoistway. When detected, the ARG engages the rail guides to counteract the vibration, delivering a smooth and refined ride when compared to conventional roller guides.

Expected Reduction Rate

VIBRATION ACCELERATION [mg]	REDUCTION RATE %
less than 5	10 - 20
greater than 5 less than 8	20 - 30
greater than 8 less than 12	30 - 40
greater than 12	40 - 50

Construction



ARG

CASE STUDY

The following information was compiled while performing vibration reduction rate tests on three Fujitec global installations with similar applications.

[NOTE: An expected vibration variance/ tolerance level with standard Fujitec roller guides is between 4 - 20 mg compared with the Fujitec ARG which is between 3.5 - 12 mg.]

Vibration Data

The data in Figure 1 includes actual side-to-side vibration readings from ONE 57 (CARNEGIE 57) in New York City. These readings were collected before and after Fujitec's ARG was installed, with their results denoted in black and red.





Figure 1 ● Standard Fujitec Roller ● Fujitec ARG

Vibration Results

Results of the case study in Figure 2, include the front-to-back and side-to-side vibration results of the cab while ascending and descending. The VIBRATION REDUCTION percentages are an average of these two variables.

PROJECT	LOCATION	SPEED	CAB DIRECTION	VIBRATION REDUCTION
One 57 (Carnegie 57)	USA	1600 ft/min	▲	45%
			▼	31%
Citibank Plaza	Hong Kong	1600 ft/min	▲	45.5%
			▼	39.5%
Garden Air tower	Japan	1400 ft/min	▲	40%
			▼	23.5%

Figure 2



ZEXIA REXIA

GS ESCALATOR
8000-NX

GS8000-HV

GS AUTOWALK
8100

EZSHUTTLE
Destination Floor Guidance System

FUJITEC

FUJITEC SINGAPORE CORPN. LTD.

204 Bedok South Avenue 1
Singapore 469333

Main Line: +65 62416222

Fax: +65 64447626

Email: fujitec.fsp@sg.fujitec.com



www.fujitecsg.com